



Bring you a global solution

Our main aim is to answer all specific requirements of your installation by bringing you a global solution. CASTEL can offer you multiple complementary accessories for its intercom and access control systems ranges.

VIDEO



MONITEUR COUL 10"
Colour Monitor 10" VGA and BNC
REF 310.0000



MONITEUR COUL 21"
Colour Monitor 21" VGA and BNC
REF 310.0100

ALIM MONITEUR 10"
10" colour monitor power supply
(230V/12V 1.2A)
REF 310.0010



DISTRIB VIDEO 1E/8S
Video distributor 1 input and 8 outputs
REF 310.1100



DVR 8 CH
Numeric multiplexer 8 channels without
hard drive and 8 alarm inputs
REF 310.2000

DVR 16 CH
Numeric multiplexer 16 channels
without hard drive and 16 alarm inputs
REF 310.2100



KIT EMETTEUR/RECEPTEUR
Transmitter receiver Balun video kit,
1 pair Cat 5
REF 310.3000



ENCODEUR VIDEO IP
Convert an analog video signal (analog
intercom station camera) to an IP video
signal
REF 310.4100

INTRUSION



DETECTEUR BI VOLU
Dual technology volumetric detector
(IR and Microwave) with three-function
hemispherical Fresnel lens - NFA2PREF
REF 320.0010



ROTULE DETECTEUR
Patented orientable ball joint for wall
or ceiling installation
REF 320.0110



DETECTEUR DOUB TECH EXT
Outdoor dual technology detector - IR
and microwave
REF 320.0500



SIRENE INT
Indoor NFA2P siren with battery
REF 320.0300



SIRENE EXT
Outdoor NFA2P siren with battery
REF 320.0600



ALIM 12V 2.2A
12VDC 2.2A saved power supply -
battery 17 Ah
REF 320.0400



CONTACT DE PORTE
Magnetic contact for surface mounting -
for door/window frames
REF 320.0200



CONTACT DE PORTE NFA2P
Magnetic contact for flush mounting -
for door/window frames - NFA2P
REF 320.0900




DETECTEUR D'OUVERTURE NFA2P
Magnetic contact for surface mounting -
for door/window frames - NFA2P
REF 320.1000



CONTACT DE SOL SABOT
Magnetic contact for sliding/pivoting
doors - NFA2P
REF 320.1100



DETECTEUR BRIS DE VERRE
Glass break detector
REF 320.0800



TRANSMETTEUR TEL
Telephone transmitter - 8 inputs -
4 numbers - voice and digital
transmission
REF 320.5000



TRANSMETTEUR TEL SERIAL
Telephone transmitter - 4 numbers
(partial mode) or unlimited (Full mode) -
voice and digital transmission
REF 320.5100





Accessories

ACCESS CONTROL



CLAVIER AUTONOME

Polycarbonate standalone coded keyboard (IP65) with 2 relays - 1 buzzer
REF 330.0000


- > Blue backlight keys - 3 Leds
- > Tamper function
- > Programming through the front panel via a master code
- > Capacity: 100 user codes
- > Dimensions 120 x 36 x 83 mm - Power supply 12/24V 0,25V not included



CLAVIER AUTONOME AV

Zamak standalone coded keyboard (IP65 - IK10) with 2 relays - 1 buzzer
REF 330.0050

- > Blue backlight keys - 3 Leds
- > Tamper function
- > Programming through the front panel via a master code
- > Capacity: 100 user codes
- > Dimensions 120 x 36 x 83 mm
- > Power supply 12/24V 0,25V not included



CLAVIER AUTONOME BRAILLE

Standalone coded keyboard with backlit keys with Braille diameter 16 mm (blue)
REF 330.0200

- > 2 relays - Led and operating buzzer
- > Stainless steel vandal proof front panel
- > Flush mounted
- > Programming through the front panel via a master code
- > Dimensions 135 x 100 x 2,5 mm (flush-mounted with flush box D 40 mm)
- > 140 x 105 x 60 mm (surface-mounted with optional surface box REF 330.0150)
- > Power supply 12V not included



GACHE 128 SS TET 10/24V

Stationary contact fail secure electrical strike
REF 320.1700

- > Height 66mm
- > Width 16mm
- > Depth 25,5mm
- > 10/24V



GACHE 128 E SS TET 10/24V

Stationary contact fail secure electrical strike
REF 320.1800

- > Manual opening
- > Height 66mm
- > Width 16mm
- > Depth 25,5mm
- > 10/24V

EQUERRE DE MONTAGE TYPE L

Angle bracket for surface mounting magnetic lock
REF 320.1400

EQUERRE DE MONTAGE TYPE L+Z

Angle bracket L and Z combine for surface mounting magnetic lock
REF 320.1500



BP SORTIE

Push button
REF 330.1000

- > Integration inside housing box Ø 60 mm
- > Brush stainless steel front
- > Laser engraving «door»
- > Dimensions 90 x 90 x 1,5 mm



BP SORTIE H ZAMAK

Zamak push button (IP54 - IK09)
REF 330.1200

- > Compliant with disability regulations
- > Sound information through a buzzer and a green led for door opening information
- > Permanent blue led lighting
- > Braille marking and «door» screen printing
- > Integration inside housing box Ø 60 mm
- > Optional base for surface mounting REF 330.1250
- > Dimensions 90 x 90 x 24 mm (96 x 95 x 39 mm with base)
- > Power supply 12/24V not included



BBGV DOUBLE CONTACT

Green coverless manual trigger with 2 contacts
REF 320.3000

CARDS PERSONNALISATION



IMPRIMANTE

Plastic card printer ZN1U0000RS ZENIUS
REF 330.5000



IMPRIMANTE DF

Plastic card printer PM1H0000RD PRIMACY (double face)
REF 330.5700



LOGICIEL PRO

eMedia-CS Software professional version
REF 330.5100



VENTOUSE ENCASTRE 300KG 24V

Magnetic lock flush mounting standard compliant NFS61937
REF 320.1200

- > Holding power 3000N
- > Length 230 mm
- > Width 38mm
- > Depth 27mm
- > 24V



VENTOUSE APPLIQUE 300KG 24V

Magnetic lock surface mounting standard compliant NFS61937
REF 320.1300

- > Holding power 3000N
- > Length 250mm
- > Width 42mm
- > Depth 25mm
- > 24V



WEB CAM

Web quick pro webcam
REF 330.5400

RUBAN

5 panel colour ribbon YMCKO (for 100 printing)
REF 330.5200

KIT NETTOYAGE

Cleaning kit Regular ACL001 (for 1000 printing)
REF 330.5300

LACET

Plastic card holder lanyard
REF 330.5500

PORTE BADGE


Plastic card holder
REF 330.5600






Accessories

POWER SUPPLIES



RACK ALIM 24V24A

24V 24A (rack) saved power supply - (batteries)
REF 350.1000




RACK ALIM 12V24A

12V 24A (rack) saved power supply - (batteries)
REF 350.1100



COFF ALIM 24V16A

24V 16A (boxed) saved power supply - (batteries)
REF 350.1200



RACK ALIM AES24V24A

AES 24V 24A (rack) saved power supply - (batteries)
REF 350.1300



ALIM AES 24V 3A S

AES 24V 3A 7Ah saved power supply - (batteries) standards compliant NFS 61940
REF 350.1400




ALIM A24V 6A S

24V 6A (boxed) saved power supply - (batteries)
REF 350.1500



CONV 24/12V

24/12VDC 3A converter
REF 350.1600



A12V-3AS

12V 3A saved power supply - (batteries)
REF 350.1700

A24V-3A5-S8.5

24 VDC 3A saved power supply with batteries 8.5 Ah
REF 110.9200



A12V-1.25A

12 VDC 1.25A power supply (switch mode). Din rail mounting
REF 110.9300

AUDIO



HP/MICRO USB

Jabra Speak 410 MS Speakerphone USB
REF 300.0000



BOUCLE INDUCTION

Remote induction loop (integrated in ABS case and stainless steel front panel). Power supply 24V
REF 540.3100

NETWORK



IP 2 WIRES CONVERTER

Allows to connect a remote IP equipment on two wires (up to 500 meters on a twisted pair). Made of 1 module installed upstream and connected to the switch and 1 module installed downstream and connected to the remote IP equipment.
REF 310.5000

A48V-1,25A-J

48VDC 1.25A power supply including jack connector for IP 2 WIRES CONVERTER (distance > from 250m to 500m).
REF 540.6200

COLUMNS



POTELET VL XE PM

Aluminium post - Height 1,50m
- RAL colour aluminium 9006 - Ground plate mounting with 3 rawl plugs Ø 12 not provided - with a pre cut for small XE intercom unit
REF 590.9800

POTELET VL XE GM

Aluminium post - Height 1,50m
- RAL colour aluminium 9006 - Ground plate mounting with 3 rawl plugs Ø 12 not provided - with a pre cut for big XE intercom unit
REF 590.9810

POTELET VL XE SANS DECOUPE

Aluminium post - Height 1,50m
- RAL colour aluminium 9006 - Ground plate mounting with 3 rawl plugs Ø 12 not provided - without pre cut
REF 590.9880



POTELET PL XE PM

Aluminium post - Height 2,20m
- RAL colour aluminium 9006 - Ground plate mounting with 3 rawl plugs Ø 12 not provided - with a pre cut for small XE intercom unit
REF 590.9820

POTELET PL XE GM

Aluminium post - Height 2,20m
- RAL colour aluminium 9006 - Ground plate mounting with 3 rawl plugs Ø 12 not provided - with a pre cut for big XE intercom unit
REF 590.9830

POTELET PL XE SANS DECOUPE

Aluminium post - Height 2,20m
- RAL colour aluminium 9006 - Ground plate mounting with 3 rawl plugs Ø 12 not provided - without pre cut
REF 590.9890



POTELET VL/PL XE PM

Aluminium post - Height 2,20m
- RAL colour aluminium 9006 - Ground plate mounting with 3 rawl plugs Ø 12 not provided - with 2 pre cuts for small XE intercom units
REF 590.9840

POTELET VL/PL XE GM

Aluminium post - Height 2,20m
- RAL colour aluminium 9006 - Ground plate mounting with 3 rawl plugs Ø 12 not provided - with 2 pre cuts for big XE intercom units
REF 590.9850

POTELET VL CAP250

Aluminium post - Height 1,50m
- RAL colour aluminium 9006 - Ground plate mounting with 3 rawl plugs Ø 12 not provided - with a pre cut for CAP 250
REF 340.9800

POTELET VL CAP350

Aluminium post - Height 1,50m
- RAL colour aluminium 9006 - Ground plate mounting with 3 rawl plugs Ø 12 not provided - with a pre cut for CAP 350
REF 340.9810

POTELET PL CAP250

Aluminium post - Height 2,20m
- RAL colour aluminium 9006 - Ground plate mounting with 3 rawl plugs Ø 12 not provided - with a pre cut for CAP 250
REF 340.9820

POTELET PL CAP350

Aluminium post - Height 2,20m
- RAL colour aluminium 9006 - Ground plate mounting with 3 rawl plugs Ø 12 not provided - with a pre cut for CAP 350
REF 340.9830

POTELET VL/PL 2 CAP250

Aluminium post - Height 2,20m
- RAL colour aluminium 9006 - Ground plate mounting with 3 rawl plugs Ø 12 not provided - with 2 pre cuts for CAP 250
REF 340.9840

POTELET VL/PL 2 CAP350

Aluminium post - Height 2,20m
- RAL colour aluminium 9006 - Ground plate mounting with 3 rawl plugs Ø 12 not provided - with 2 pre cuts for CAP 350
REF 340.9850

