



Accessories

BRING YOU A GLOBAL SOLUTION

Our main aim is to answer all specific requirements of your installation by bringing you a global solution. CASTEL can offer you multiple complementary accessories for its intercom and access control systems ranges.

VIDEO



MONITEUR COUL 10"
Colour Monitor 10" VGA and BNC
REF 310.0000

ALIM MONITEUR 10"
10" colour monitor power supply (230V/12V 1.2A)
REF 310.0010



MONITEUR COUL 21"
Colour Monitor 21" VGA and BNC
REF 310.0100



KIT ÉMETTEUR/RÉCEPTEUR
Transmitter receiver Balun video kit, 1 pair Cat 5
REF 310.3000



DVR 8 CH
Numeric multiplexer 8 channels without hard drive and 8 alarm inputs
REF 310.2000

DVR 16 CH
Numeric multiplexer 16 channels without hard drive and 16 alarm inputs
REF 310.2100

ACCESS CONTROL



CLAVIER AUTONOME
Polycarbonate standalone coded keyboard (IP65) with 2 relays - 1 buzzer
REF 330.0000

- > Blue backlight keys - 3 Leds
- > Tamper function
- > Programming through the front panel via a master code
- > Capacity: 100 user codes
- > Dimensions 120 x 36 x 83 mm - Power supply 12/24V 0.25V not included



CLAVIER AUTONOME AV
Zamak standalone coded keyboard (IP65 - IK10) with 2 relays - 1 buzzer
REF 330.0050

- > Blue backlight keys - 3 Leds
- > Tamper function
- > Programming through the front panel via a master code
- > Capacity: 100 user codes
- > Dimensions 120 x 36 x 83 mm
- > Power supply 12/24V 0.25V not included



BP SORTIE
Exit push button
REF 330.1000

- > Integration inside housing box Ø 60 mm
- > Brush stainless steel front
- > Dimensions 90 x 90 x 1.5 mm



BP SORTIE H ZAMAK
Zamak exit push button - DDA compliant (IP54 - IK09)
REF 330.1200

- > Sound information through a buzzer and a green led for door opening information
- > Permanent blue led lighting
- > Integration inside housing box Ø 60 mm
- > Optional base for surface mounting (REF 330.1250)
- > Dimensions 90 x 90 x 24 mm (96 x 95 x 39 mm with base)
- > Power supply 12/24V not included



BBGV DOUBLE CONTACT
Green coverless manual trigger with 2 contacts
REF 320.3000



CLAVIER AUTONOME BRAILLE
Standalone coded keyboard with backlit (blue) keys with Braille diameter 16 mm - 2 relays
REF 330.0200

- > Led and operating buzzer
- > Stainless steel vandal proof front panel
- > Flush mounted
- > Programming through the front panel via a master code
- > Dimensions 135 x 100 x 2.5 mm (flush-mounted with flush box D 40 mm)
- > 140 x 105 x 60 mm (surface-mounted with optional surface box - REF 330.0150 -)
- > Power supply 12V not included



BP SORTIE SANS CONTACT
Contactless stainless steel exit push button with 2 relays - DDA compliant
REF 330.1150

- > A green led for door opening information
- > Permanent blue led lighting
- > Adjustable detection distance from 3 to 12 cm
- > Relay delay adjustable up to 27.80 seconds or bistable mode (ON/OFF)
- > Integration inside housing box Ø 60 mm
- > Optional base for surface mounting (REF 330.1170)
- > Dimensions 90 x 90 x 38 mm (96 x 95 x 43 mm with base)
- > Power supply 12/24Vdc 35mA not included

BP SORTIE SANS CONTACT BUZZER
Contactless stainless steel output button with 2 relays - DDA compliant - 1 buzzer
REF 330.1160

FOND SAILLIE BP SS CONTACT
Box for BP SORTIE SANS CONTACT surface mounting
REF 330.1170



VENTOUSE ENCASTRE 300KG 24V
Magnetic lock flush mounting standard compliant NFS61937
REF 320.1200

- > Holding power 3000N
- > Length 230 mm
- > Width 38mm
- > Depth 27mm
- > 24V



VENTOUSE APPLIQUE 300KG 24V
Magnetic lock surface mounting standard compliant NFS61937
REF 320.1300

- > Holding power 3000N
- > Length 250mm
- > Width 42mm
- > Depth 25mm
- > 24V

+ Accessories



GÂCHE 128 SS TET 10/24V
Stationary contact fail secure electrical strike
REF 320.1700

- > Height 66mm
- > Width 16mm
- > Depth 25.5mm
- > 10/24V



GÂCHE 128 E SS TET 10/24V
Stationary contact fail secure electrical strike
REF 320.1800

- > Manual opening
- > Height 66mm
- > Width 16mm
- > Depth 25.5mm
- > 10/24V

ÉQUERRE DE MONTAGE TYPE L

Angle bracket for surface mounting magnetic lock
REF 320.1400

ÉQUERRE DE MONTAGE TYPE L+Z

Angle bracket L and Z combine for surface mounting magnetic lock
REF 320.1500

BOITIER CONTROLE DE POSITION

Position control box - Equipped with a floating contact (standby position information: lock) and a floating contact (security position information: unlock)
REF 320.1600

TÉTIÈRE HZ INOX

Standard stainless faceplate with latch bolt and dead bolt opening
REF 320.1900

- > Length 250mm
- > Width 25mm
- > Thickness 3mm

CARDS PERSONALISATION



IMPRIMANTE SF
Plastic card printer (simple face) ZENIUS with cardpreso software
REF 330.5000



IMPRIMANTE DF
Plastic card printer (double faces) PRIMACY with cardpreso software
REF 330.5700

KIT NETTOYAGE

Cleaning kit Regular EVOLYS (for 1,000 printings)
REF 330.5300



WEB CAM
Web quick pro webcam
REF 330.5400

RUBAN ZENIUS

Colour ribbon ZENIUS (for 200 faces)
REF 330.5200

RUBAN PRIMACY 2

Colour ribbon PRIMACY 2 (for 300 faces)
REF 330.5250


LACET

Plastic card holder lanyard
REF 330.5500

PORTE BADGE

Plastic card holder
REF 330.5600

POWER SUPPLIES



RACK ALIM 24V24A
24V 24A (rack) saved power supply - (batteries)
REF 350.1000



RACK ALIM AES24V24A
AES 24V 24A (rack) saved power supply - (batteries)
REF 350.1300



COFF ALIM 24V16A
24V 16A (boxed) saved power supply - (batteries)
REF 350.1200

RACK ALIM 12V24A

12V 24A (rack) saved power supply - (batteries)
REF 350.1100




ALIM AES 24V 3A S
AES 24V 3A 7Ah saved power supply - (batteries) standards compliant NFS 61940
REF 350.1400



ALIM A24V 6A S
24V 6A (boxed) saved power supply - (batteries)
REF 350.1500



CONV 24/12V
24/12VDC 3A converter
REF 350.1600



A12V-3AS
12V 3A saved power supply - (batteries)
REF 350.1700

A24V-3A5-S8.5

24 VDC 3A saved power supply with batteries 8.5 Ah
REF 110.9200



A12V-1.25A
12 VDC 1.25A power supply (switch mode). Din rail mounting
REF 110.9300

AUDIO



HP/MICRO USB BLE
Jabra Speak 410 MS Speakerphone USB
REF 300.0000



BOUCLE INDUCTION
Remote induction loop (integrated in ABS case and stainless steel front panel). Power supply 24V not included.
REF 540.3100

NETWORK



IP 2 WIRES CONVERTER

Allows to connect a remote IP equipment on two wires (up to 500 meters on a twisted pair). Made of 1 module installed upstream and connected to the switch and 1 module installed downstream and connected to the remote IP equipment.
REF 310.5000

A48V-1,25A-J

48VDC 1.25A power supply including jack connector for IP 2 WIRES CONVERTER (distance > from 250m to 500m).
REF 540.6200

COLUMNS



POTELET VL XE PM

Aluminium post with a pre cut for small XE intercom unit
REF [590.9800](#)

- > Height 1.50m
- > RAL colour aluminium 9006
- > Ground plate mounting with 3 dowels Ø 12 not provided

POTELET VL XE GM

Aluminium post with a pre cut for big XE intercom unit
REF [590.9810](#)

POTELET VL XE TGM

Aluminium post with a pre cut for very big XE intercom unit
REF [590.9815](#)

POTELET VL XE SANS DECOUPE

Aluminium post without pre cut
REF [590.9880](#)



POTELET PL XE PM

Aluminium post with a pre cut for small XE intercom unit
REF [590.9820](#)

- > Height 2.20m
- > RAL colour aluminium 9006
- > Ground plate mounting with 3 dowels Ø 12 not provided

POTELET PL XE GM

Aluminium post with a pre cut for big XE intercom unit
REF [590.9830](#)

POTELET PL XE TGM

Aluminium post with a pre cut for very big XE intercom unit
REF [590.9835](#)

POTELET PL XE SANS DECOUPE

Aluminium post without pre cut
REF [590.9890](#)



POTELET VL/PL XE PM

Aluminium post with 2 pre cuts for small XE intercom units
REF [590.9840](#)

- > Height 2.20m
- > RAL colour aluminium 9006
- > Ground plate mounting with 3 dowels Ø 12 not provided

POTELET VL/PL XE GM

Aluminium post with 2 pre cuts for big XE intercom units
REF [590.9850](#)

POTELET VL PL XE TGM

Aluminium post with 2 pre cuts for very big XE intercom units
REF [590.9855](#)

FOND XE PM MONTAGE POTELET

Mounting bottom XE intercom small version for assembly on no Castel post
REF [590.9860](#)

FOND XE GM MONTAGE POTELET

Mounting bottom XE intercom large version for assembly on no Castel post
REF [590.9870](#)

FOND XE TGM MONTAGE POTELET

Mounting bottom XE intercom very large version for assembly on no Castel post
REF [590.9875](#)



POTELET VL XLESS

Aluminium post with a pre cut for Xless intercom unit
REF [340.9860](#)

- > Height 1.50m
- > RAL colour aluminium 9006
- > Ground plate mounting with 3 dowels Ø 12 not provided



POTELET PL XLESS

Aluminium post with a pre cut for Xless intercom unit
REF [340.9870](#)

- > Height 2.20m
- > RAL colour aluminium 9006
- > Ground plate mounting with 3 dowels Ø 12 not provided



POTELET VL/PL XLESS

Aluminium post with 2 pre cuts for Xless intercom units
REF [340.9880](#)

- > Height 2.20m
- > RAL colour aluminium 9006
- > Ground plate mounting with 3 dowels Ø 12 not provided